



SAFETY DATA SHEET WICKES DANISH OIL

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME	WICKES DANISH OIL
PRODUCT NO.	190953
SYNONYMS, TRADE NAMES	WN 10889
APPLICATION	Protective coating
SUPPLIER	Wickes Building Supplies Ltd, Wickes House, 120/138 Station Road, Harrow. HA1 2QB 0208 901 2000 0870 608 9001 (Customer Services) 0208 427 1645
EMERGENCY TELEPHONE	Tel: 0208 901 2000

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
Cobalt 2-Ethylhexanoate	237-015-9	13586-82-8	< 1%	Xi;R38. R43.
ETHYL METHYL KETOXIME	202-496-6	96-29-7	< 1%	Carc3;R40 Xn;R21 R43 Xi;R41
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY.	265-150-3	64742-48-9	25-50%	Xn;R65. R10,R66.
WHITE SPIRIT	265-185-4	64742-82-1	10-25%	Xn;R65. N;R51/53. R10,R66.

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Flammable. Repeated exposure may cause skin dryness or cracking. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION R10, R52/53, R66.

4 FIRST-AID MEASURES

GENERAL INFORMATION

Remove affected person from source of contamination. Provide rest, warmth and fresh air. Place unconscious person on the side in the recovery position and ensure breathing can take place. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

INHALATION

General first aid, rest, warmth and fresh air. Place unconscious person on the side in the recovery position and ensure breathing. If breathing stops, provide artificial respiration. NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Get medical attention if any discomfort continues.

INGESTION

Provide rest, warmth and fresh air. DO NOT induce vomiting. Get medical attention immediately.

SKIN CONTACT

Remove contaminated clothing. Wash skin thoroughly with soap and water. Contact physician if irritation continues.

WICKES DANISH OIL

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Water spray, fog or mist. Alcohol resistant foam. Carbon dioxide (CO₂). Do not use water jet as an extinguisher, as this will spread the fire.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. NOTE! Use air-supplied respirators to protect against gases/fumes. Cool containers exposed to flames with water until well after the fire is out. Move container from fire area if it can be done without risk. Keep run-off water out of sewers and water sources. Dike for water control.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. When dealing with a spillage, please consult the section relating to suitable protective measures. Wear necessary protective equipment. Provide ventilation and confine spill. Do not allow runoff to sewer. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Wash thoroughly after dealing with a spillage. Inform Authorities if large amounts are involved.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Risk of vapour concentration on the floor and in low-lying areas. Provide good ventilation. Keep away from heat, sparks and open flame. During application and drying, solvent vapours will be emitted. Avoid spilling, skin and eye contact. Avoid inhalation of vapours/spray and contact with skin and eyes. Avoid inhalation of dust. Do not use in confined spaces without adequate ventilation and/or respirator. Avoid eating, drinking and smoking when using the product. Contaminated rags and cloths must be put in fireproof containers for disposal.

STORAGE PRECAUTIONS

Store at moderate temperatures in dry, well ventilated area. Store below 25°C. Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep in original container. Keep upright.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m ³	ST - ppm	ST - mg/m ³
Cobalt 2-Ethylhexanoate	WEL	No std.	0.1 mg/m ³	No std.	No std.
ETHYL METHYL KETOXIME		No std.	No std.	No std.	No std.
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY.	SUP	1000 ppm	No std.		No std.
WHITE SPIRIT	SUP		350 mg/m ³		

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits SUP = Supplier's recommendation. EU = Indicative Values according to Commission Directive 91/322/EEC.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours. Must not be handled in confined space without sufficient ventilation.

RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided.

HAND PROTECTION

Protective gloves should be used if there is a risk of direct contact or splash. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

WICKES DANISH OIL

OTHER PROTECTION

Wear appropriate clothing to prevent reasonably probable skin contact.

HYGIENE MEASURES

Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. Wash contaminated clothing before reuse. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Light viscous liquid
COLOUR	Light brown to Brownish
ODOUR	Characteristic Hydrocarbon Solvent.
SOLUBILITY	Immiscible with water
FLASH POINT (°C)	41

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions. No particular stability concerns.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong mineral acids. Strong alkalis. Oxidising materials.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Fire creates: Carbon dioxide (CO₂). Carbon monoxide (CO). Oxides of: Nitrogen.

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

Knowledge about health hazard is incomplete. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

INHALATION

Vapours may cause headache, fatigue, dizziness and nausea. Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication. When working extensively on big surfaces in small and badly ventilated rooms, vapours may develop in concentrations which may cause headache and irritation of the eyes and the respiratory system.

SKIN CONTACT

Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause sensitisation by skin contact. May be absorbed through the skin.

EYE CONTACT

Vapour or spray may cause temporary (reversible) eye damage.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

There are no data on the ecotoxicity of this product. Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

DEGRADABILITY

There are no data on the degradability of this product.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Do not allow runoff to sewer, waterway or ground. Dispose of waste and residues in accordance with local authority requirements. Contact specialist disposal companies.

14 TRANSPORT INFORMATION

WICKES DANISH OIL



PROPER SHIPPING NAME	PAINT		
UN NO. ROAD	1263	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	UN NO. SEA	1263
IMDG CLASS	3	IMDG PACK GR.	III
EMS	F-E; S-E	MARINE POLLUTANT	



15 REGULATORY INFORMATION

RISK PHRASES

R10	Flammable.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.

SAFETY PHRASES

P14	Contains Cobalt 2-Ethylhexanoate,ETHYL METHYL KETOXIME. May produce an allergic reaction.
S2	Keep out of the reach of children
S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S28	After contact with skin, wash immediately with plenty of water.
S37	Wear suitable gloves.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations.

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION COMMENTS

Ver. 0

SDS NO. 10889/0

SAFETY DATA SHEET STATUS

Approved.

WICKES DANISH OIL

DATE 24-01-2007

RISK PHRASES IN FULL

- R10 Flammable.
- R21 Harmful in contact with skin.
- R38 Irritating to skin.
- R40 Limited evidence of a carcinogenic effect.
- R41 Risk of serious damage to eyes.
- R43 May cause sensitisation by skin contact.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.